



SLURRY REMOVER

UPDATE

March 29, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Bare surfaces
- Concrete or clay pavers and slabs

PROPERTIES

- Removes cement slurry and polymeric sand haze
- For bare surfaces, concrete or clay pavers and slabs

DESCRIPTION

Removes cement slurry and polymeric sand haze on bare surfaces such as concrete or clay pavers and slabs.

DIRECTIONS

Read the Material Safety Data Sheet before using this product. Wear acid-resistant clothing, boots, gloves and safety goggles.

1. DILUTION: Principle: To use the strongest concentration of product without etching or discolouring pavers. A weaker concentration will increase the labor factor.

1. Into a plastic watering can dilute 1 part product in 8 or more parts water.

2. Test the concentration on spare pavers or on a small hidden area of approximately 0.4 m² (4 sq. ft.). Test area or spare pavers must be wet.

- If the product etches or discolours the pavers: lower the concentration (1 part product in 10 parts water) until the product no longer etches or discolour the pavers.

- If the product DOES NOT etch or discolours the pavers: to increase product efficiency and reduce scrubbing, you may use a stronger concentration. The concentration must be strong enough to remove slurry without etching or discolouring pavers.

IMPORTANT: Always test diluted product before using on the entire surface.

ALWAYS POUR THE SLURRY REMOVER INTO WATER; NEVER POUR WATER INTO THE PRODUCT.

2. WETTING: To prevent product penetration and make rinsing easier, first saturate surface with water. Always work on a wet surface.

3. APPLICATION: Do not use on flagstone or on natural stone.

Cement slurry on concrete pavers or slabs:

1. If application is done on pavers with new polymeric sand joints, wait 30 days before applying the product.

2. Using a plastic watering can, cover the cement slurry with SLURRY REMOVER. Work in small areas.

3. Lightly scrub.

4. Rinse immediately and thoroughly.

Product should not sit on the surface more than a few seconds.

Polymeric sand haze on concrete pavers or slabs:

1. If application is done on pavers with new polymeric sand joints, wait 30 days before applying the product.
2. Work in small sections; no more than 4.6 m² (50 sq. ft.).
3. Using a plastic watering can, cover the area with SLURRY REMOVER.
4. Lightly scrub.
5. Rinse immediately and thoroughly.
6. Move on to the next section.

Product should not sit on the surface more than a few seconds.

IMPORTANT: DO NOT let product dry on the surface. If product dries on the surface, reapply product, lightly scrub and rinse immediately and thoroughly. **TIP:** To improve efficiency on large areas, 3 persons are recommended to apply the product. One person should spray (pour) the product while another is scrubbing and a third is rinsing.

STORAGE

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink.

COVERAGE

4 L of concentrated product clean up to 56 m² (600 sq. ft.). Coverage will depend on surface condition and product dilution.

PACKAGING

Product code	Size	Units per box	Units per pallet
60200241 (241-554)	4 L	4	144
60200242 (241-556)	18.93 L	—	48

WARNING

CAUSES SEVERE RESPIRATORY TRACT, EYE AND SKIN BURNS. HARMFUL IF INHALED. FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. Do not mix with Alkali. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Handle with care. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection: Chemical splash goggles or face shield. Use chemical-resistant, impervious gloves. Wear appropriate respirator when ventilation is inadequate. **FIRST AID TREATMENT Contains:** Hydrogen chloride. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

SHIPPING

Land and sea

UN1789

Hydrochloric acid

Class: 8

PG: 2

LIMITED WARRANTY

TECHNISEAL® warrants the Slurry Remover against manufacturing defects. As TECHNISEAL® has no control over surface preparation and product application, results cannot be guaranteed. The TECHNISEAL® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice: User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 0.4 m² (4 sq.ft.) area. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq.ft.).