

Hanover® Flexible Leveling Shims & Spacer Tabs

Material Safety Data Sheet

date of issue:
August 2000

version:
2.0

SECTION I. GENERAL INFORMATION

PRODUCT NAME: NATURAL AND BLACK SARLINK® 3135, 3140, 3150, 3160, 3170, 3180, 3190, 3139D & 3145D

CHEMICAL NAME & SYNONYMS: POLYOLEFIN ELASTOMER BLEND, THERMOPLASTIC ELASTOMER (TPE)

CAS REGISTRY NUMBER: PROPRIETARY BLENDS. NOT IDENTIFIED BY BY CAS #. COMPONENTS OF THESE PRODUCTS ARE LISTED UNDER TSCA CHEMICAL SUBSTANCES INVENTORY. BLACK GRADES CONTAIN CARBON BLACK. CAS #1333-68-4

Hanover Architectural Products
5000 Hanover Road
Hanover, PA 17331
www.hanoverpavers.com

717.637.0500
800.426.4242
717.637.7145 fax

SECTION II. PHYSICAL DATA

Physical State:	solid	Boiling Point:	not applicable, solid material
Odor and Appearance:	no odor; pellets	Melting Point:	softens at 150°C (320°F)
Odor Threshold:	no applicable	pH:	not applicable
Specific Gravity:	0.93 - 0.98	Coefficient of Oil/Water:	not established
Vapor Pressure:	not applicable, non-volatile material	Distribution Solubility	
Vapor Density:	not applicable, non-volatile material	in Water at 20°C:	insoluble, not applicable
Evaporation Rate:	not applicable, non-volatile material		

SECTION III. FIRE OR EXPLOSION HAZARD DATA

Flash Point: Not established

Auto Ignition Temperature: Not established

Flammable Limits: Not applicable, non-volatile material

Hazardous Combustion Products: Carbon monoxide, products from incomplete combustion and various hydrocarbon compounds

Extinguishing Media: Use Carbon dioxide, water fog, foam or dry chemical.

Special Firefighting Procedures: Firefighters must wear full-face positive-pressure, self-contained breathing apparatus to provide protection against combustion products. Evacuate all unprotected personnel.

Unusual Fire and Explosion Hazards: Small amounts of fines of products may be formed. Every effort should be made to prevent the accumulation of fines in material handling systems. Equipment and conveying lines must be well grounded to eliminate any build-up of static electricity.

NFPA Rating: Health = 1 (slight)
Fire = 1 (slight)
Reactivity = 0 (Insignificant)

SECTION IV. REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Temperatures over 260°C (500°F) may cause degradation. Avoid ignition source.

Materials to Avoid: Strong oxidizing agents: Polyacetal resins at processing temperature.

Hazardous Decomposition Products: Carbon monoxide, various hydrocarbons, products from incomplete combustion.

Hazardous polymerization: Will not occur.

SECTION V. REGULATORY HAZARD, HEALTH INFORMATION

OSHA:	These products are not hazardous under Hazard Communication Standard 29 CFR part 1910.1200 (see note below).
WHMIS:	These products are not hazardous as defined in Canadian WHMIS Regulations.
DOT/TDG	Not regulated by U.S. Department of Transportation and Canadian Transportation of Dangerous Goods Regulations.
SARA Title III:	These products contain no known toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.
TSCA:	All ingredients are on the TSCA Chemical Substance Inventory.
CEPA:	Components of these products are included in Canada's DSL (Domestic Substance List).

Note: Black grades contain carbon black, which is considered a nuisance dust hazard by OSHA 29 CFR 1910.1000 Subpart Z-1. However, carbon black incorporated into the thermoplastic elastomers in the form delivered, is no longer believed to be a nuisance dust hazard by DSM Thermoplastic Elastomers.

SECTION VI. TOXICOLOGICAL AND HEALTH DATA

Specific Hazard: No acute or chronic hazards or effects are anticipated from the products at ambient temperature. However, at processing temperature, the products can emit fumes and vapors which may cause irritation of the eyes and respiratory tract. Good industrial hygiene and safety practices are always recommended.

Routes of Exposure:

Eye Contact: Not a probable route of exposure. Particulates may scratch eye surface or cause irritation.

Skin contact: Not an anticipated hazard at ambient temperature.

Ingestion: Not a probable route of exposure.

Inhalation: Not a probable route of exposure under conditions of normal use. Hot fumes or vapors which may form during processing can cause irritation to the respiratory tract.

Toxicology Information:

Carcinogenicity:	None reported
Mutagenicity:	None reported
Reproductive Effects:	None reported
Teratogenicity:	None reported
LD50/LC50 data:	No test data available

Additional Information:

Note 1. Representative grades were rated non-toxic in a cytotoxicity testing.

Note 2. Representative grades met the requirements of a USP class VI material.

SECTION VII. PROTECTIVE AND PREVENTATIVE MEASURES

Personal Protective Equipment:

Eye: Wear safety glasses or chemical goggles

Skin: Wear protective gloves when handling elastomer bags or hot material during processing

Respiratory: Not normally required at ambient temperature. If processing in area where ventilation is inadequate, wear NIOSH approved organic vapor respirator with mechanical filtration. If processing conditions generate large amounts of dust, wear NIOSH approved respirator for nuisance dust.

Handling Procedures and Equipment: Practice good personal hygiene. Avoid eye contact. Avoid inhalation of fumes or vapors. Avoid generation and prolonged breathing of dust.

Engineering Controls:	Local exhaust ventilation is recommended during all hot processing operations.
Exposure Guidelines:	Not established.

SECTION VIII. EMERGENCY AND FIRST AID PROCEDURES

Inhalation: If respiratory irritation occurs, remove affected personnel from the work area. Obtain medical attention if irritation persists or if severe. Implement appropriate controls to prevent further exposures.

Ingestion: Consult a physician if pain or discomfort occurs.

Eyes: Remove dust particles by flushing eye with clean water. Seek medical attention.

Skin: Wash contaminated skin with mild soap and water. Should a burn occur, cool burn area immediately with cool, clean running water until no heat is emitted from burn area. Cover with light, dry dressing. Obtain medical assistance.

SECTION IX. SPILLS, DISPOSAL, STORAGE GUIDELINES

Spill and Release Information: Repackage uncontaminated elastomer. Reuse or dispose of as noted below if contaminated.

Disposal Information: Reuse if possible. Dispose in accordance with local, state and federal regulations and applicable environmental regulation. Material as supplied is not characterized as hazardous under RCRA (Resource and Conservation Recovery Act).

Storage: Store at ambient temperature, in dry area and in the absence of direct sunlight.

HANOVER[®]
Architectural Products
5000 Hanover Road, Hanover, PA 17331
717.637.0500 • fax 717.637.7145
www.hanoverpavers.com