



GATOR XP SAND BOND
FOR CONCRETE PAVERS JOINTS
MSDS Revision Date (dd/mm/yyyy): 04/04/2012

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1 - PRODUCT & COMPANY IDENTIFICATION

Product name : GATOR SUPER SAND BOND
Supplier : Alliance Designer Products Inc.
225 Blvd Bellerose West
Laval, Quebec
Canada
H7L 6A1
www.alliancegator.com
24 hour Emergency Phone : Chemtrec 1-800-424-9300
Chemical Family : Silica & Granite
Product use : Joint Material.
Hazard Rating :
Health :1
Fire :0
Reactivity :0

SECTION 2 - COMPOSITION - INGREDIENTS INFORMATION

Ingredient	CAS #	%	Exposure Limit	LD ₅₀	LD ₅₀
Crystalline Silica (Quartz)	14808-60-7	Min 4%	0.05 mg/m ³ TWA ACGIH	Not Available	Not Available

Balance of ingredients are non-hazardous

SECTION 3 - HAZARDS IDENTIFICATION

Description : Buff (beige, slate grey or ivory) colored granules, Slight odor.
Hazards : WARNING! HARMFUL IF INHALED, OVEREXPOSURE MAY CAUSE LUNG DAMAGE, MAY CAUSE EYE IRRITATION CANCER HAZARD. CONTAINS QUARTZ WHICH CAN CAUSE CANCER.
Precautions : Risk of cancer depends upon duration and level of exposure.
Primary Routes of Entry : Avoid breathing dust, contact with skin and eyes.
Signs and Symptoms of Exposure : Eye, Inhalation, Skin Contact.
Inhalation of quartz is classified as a human carcinogen. Chronic Exposure can cause silicosis, a form of lung scarring that can cause Shortness of breath, reduced lung fonction, and in severe cases, death. Inhalation may increase the progression of tuberculosis, susceptibility is apparently not increased. Persons with impaired respiratory fonction may be more susceptible to the effects of this substance. Smoking can increase the risk of lung injury.
Target Organs : Lungs

SECTION 4 - FIRST AID MEASURES

Ingestion : Get immediate medical attention.
Never give anything by mouth to an unconscious person.
Dilute with water. Keep patient warm and calm.
Induce vomiting only on the instructions of a health care professional.

Skin : Remove contaminated clothing.
Rinse thoroughly with plenty of water.
If irritation occurs or persists consult a doctor.



GATOR XP SAND BOND
FOR CONCRETE PAVERS JOINTS
MSDS Revision Date (dd/mm/yyyy): 04/04/2012

SECTION 4 - FIRST AID MEASURES (CONT.)

Inhalation : Remove victim to fresh air. If breathing is difficult or has stopped, a properly trained person should administer oxygen or artificial respiration.
Get immediate medical attention.

Eyes : Immediately flush eyes with plenty of water, holding eyelids apart during flushing.
Obtain immediate medical attention.

In case of overexposure – Always bring a copy of the product MSDS to the Doctor.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not applicable.

Flash Point Test Method : Not applicable.

Explosion Limits : Not applicable.

Fire and Explosion Hazards : None.

Fire Fighting Instructions : Wear self-contained breathing apparatus and full bunker gear.

Extinguishing Media : Not required.

Hazardous Combustion Products : None.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill and Leak : Avoid generating dust. Wear respiratory protection. Sweep up or Vacuum and place in properly identified container.

SECTION 7 - HANDLING AND STORAGE

Handling Instructions : Avoid skin and eye contact. Avoid generation dust. DO NOT BREATHE DUST. Maintain good personal hygiene and wash Thoroughly after handling, especially before eating, drinking or smoking. Wash contaminated clothing before reuse.

Storage Measures : Store in a cool, dry and well-ventilated area. Store away from heat Sources or open flames. Store away from incompatible materials. Keep containers tightly closed when not in use.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Skin Protection : Wear protective gloves and long sleeve shirts to prevent skin contact.

Eye Protection : Wear safety goggles.

Respiratory Protection : In poorly ventilated areas or if the exposure limits discribed in section 2 Are likely to be exceeded then wear a high efficiency particulate Respirator (NIOSH type N100 filter).

Engineering Controls : Adequate local exhaust ventilation at point of emission.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Solid (Powder).

Colour : Beige, Slate Grey & Ivory.

Odour : None.

Odour Threshold : None.

Solubility in Water : Insoluble.

Vapour Pressure : Not applicable.

Evaporation Rate : Not applicable.

Vapour Density : No data.

Specific Gravity : 2.65.

Boiling Point (°C) : 2230°.

Alliance Designer Products Inc.



GATOR XP SAND BOND
FOR CONCRETE PAVERS JOINTS
MSDS Revision Date (dd/mm/yyyy): 04/04/2012

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES (CONT.)

Freezing/Melting Point (°C) : 1710°
pH : No data.
Volatiles (%) : <1.0.
Coefficient Water/Oil : No data.

SECTION 10: STABILITY AND REACTIVITY

Conditions to Avoid : Exposure to excessive heat.
Material to Avoid : Strong alkalis, hydrofluoric acid, powerful oxidizers, and fluorine. Containing compounds.
Stability : Product is stable in non-emergency conditions.
Hazardous Polymerization : Will not occur.
Hazardous products of decomposition: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

LD₅₀ (species/route) : 266 000 mg/kg rat.
LC₅₀ (species/duration) : 50 000 mg/m³ rat (96 hours).
Exposure Limits : See Section 2.
Irritation : Mild.
Sensitization : None reported.
Carcinogenicity : No potential occupational carcinogen.
IARC Category 1 Carcinogen
NTP!: Yes
Reproductive Effects : No reported.
Teratogenicity : No reported.
Mutagenicity : No reported.
Synergistic : No reported.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate : No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste disposal Method : Dispose in a manner consistent with local, regional, provincial and/or Federal regulations.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name : Not regulated.
UN # : Not applicable.
Class(es) : Not applicable.
Packaging Group : Not applicable.
Other information : None.
Transport Emergency : In the event of a transport emergency contact CHEMTREC at 1 800 424-9300.

SECTION 15 - REGULATORY INFORMATION

WHMIS Classification : Not controlled.
CEPA Status : Appears on the DSL.
TSCA : Appears on the TSCA Inventory.
Other : This product is know to the State of California to cause cancer.

Alliance Designer Products Inc.



GATOR XP SAND BOND
FOR CONCRETE PAVERS JOINTS
MSDS Revision Date (dd/mm/yyyy): 04/04/2012

SECTION 16 - DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

SECTION 17 - OTHER INFORMATION

MSDS # 2003-01 Revision # 5 Revision Date : April 2012