

DIMENSIONALLY COMPATIBLE HANOVER® PREST® PAVER SIZES

		1 1/4"	1 1/2"	1 3/4"	1 13/16"	2"	2 1/4"	2 1/2"	3"	4"
150mm x 447mm	5 7/8" x 17 5/8"					X	X	X	X	X
150mm x 597mm	5 7/8" x 23 1/2"					X	X	X	X	X
150mm x 897mm	5 7/8" x 35 3/8"					X	X	X	X	X
297mm x 297mm	11 3/4" x 11 3/4"		X	X	X	X	X	X	X	
297mm x 447mm	11 3/4" x 17 5/8"		X	X		X	X	X	X	
297mm x 597mm	11 3/4" x 23 1/2"		X	X	X	X	X	X	X	
297mm x 897mm	11 3/4" x 35 3/8"		X			X	X	X	X	
447mm x 447mm	17 5/8" x 17 5/8"		X	X	X	X	X	X	X	X
447mm x 597mm	17 5/8" x 23 1/2"		X	X	X	X	X	X	X	
447mm x 897mm	17 5/8" x 35 3/8"		X			X	X	X	X	
597mm x 597mm	23 1/2" x 23 1/2"		X	X	X	X	X	X	X	X
597mm x 897mm	23 1/2" x 35 3/8"			X	X	X	X	X	X	
597mm x 1197mm	23 1/2" x 47 1/8"*							X	X	
897mm x 897mm	35 3/8" x 35 3/8"*							X	X	

ADDITIONAL HANOVER® PREST® PAVER SIZES

		1 1/4"	1 1/2"	1 3/4"	1 13/16"	2"	2 1/4"	2 1/2"	3"	4"
302mm x 302mm	11 7/8" x 11 7/8"		X			X	X	X	X	
303mm x 303mm	11 15/16" x 11 15/16"		X			X	X	X	X	
378mm x 378mm	14 7/8" x 14 7/8"		X			X	X	X	X	
403mm x 403mm	15 7/8" x 15 7/8"		X			X	X	X	X	
454mm x 454mm	17 7/8" x 17 7/8"		X			X	X	X	X	
597mm x 747mm	23 1/2" x 29 1/2"				X	X	X	X	X	
606mm x 606mm	23 7/8" x 23 7/8"		X			X	X	X	X	
606mm x 911mm	23 7/8" x 35 7/8"		X			X	X	X	X	
759mm x 759mm	29 7/8" x 29 7/8"					X				
908mm x 908mm	35 3/4" x 35 3/4"*							X	X	
911mm x 911mm	35 7/8" x 35 7/8"*							X		
Hexagonal, 402mm across flats	Hexagonal, 15 7/8" across flats					X	X	X	X	
Hexagonal, 597mm across flats	Hexagonal, 23 1/2" across flats					X	X	X	X	
Octagonal, 402mm across flats	Octagonal, 15 7/8" across flats					X	X	X	X	

MISCELLANEOUS HANOVER® ROOF PAVER SIZES

		1 1/4"	1 1/2"	1 3/4"	1 13/16"	2"	2 1/4"	2 1/2"	3"	4"
Lightweight Roof Ballast : 15 lbs/sf										
297mm x 597mm	11 3/4" x 23 1/2"	X								
597mm x 597mm	23 1/2" x 23 1/2"	X								
Pedestal® Paver : 22 lbs/sf										
597mm x 597mm	23 1/2" x 23 1/2"						X			
Special Size Paver for Roof Ballast Application : 29 lbs/sf										
908mm x 908mm	35 3/4" x 35 3/4"						X			
Special Size Paver for Pedestrian Urban Application : 32 lbs/sf										
908mm x 908mm	35 3/4" x 35 3/4"							X		

 = Standard Thickness

 = SlateFace® Paver Thickness (22 lbs/sf)

 = Natural Diamond Roof Paver Thickness (23 lbs/sf)

*Note increased thickness and weight for these paver sizes.

Please Note: Paver weight at a 2" thickness is 25 lbs/sf.

Standard manufactured thickness for pedestrian applications is 2". However, when utilized in urban pedestrian applications, a 2 1/2" thickness is recommended. The additional strength will help to accommodate the unpredictable circumstances and stressful situations that exist in the urban city environment. Contact Hanover® for a full list of paver sizes and their available thicknesses appropriate for the intended use.