

HANOVER® HIGH DEFINITION SEALER

For Paver and Sand Joints



- Deepens and sharpens color
- Protects against oil, dirt, food, grease, marker and paint penetration on paver surface
- Makes surface easy to clean
- Reinforces joints by keeping sand in place
- Minimizes erosion and weed growth

A PROTECTING SEALANT THAT ALLOWS BREATHABILITY OF THE CONCRETE MASONRY OR PAVER UNIT

Hanover® HD Sealer enhances the appearance of the architectural concrete masonry units. It is impervious to liquids, yet is vapor/air permeable. HD Sealer forms a long lasting protection barrier from water, dirt, oil and UV light while allowing the paver surface to breathe. Color is deeply intensified, simulating the appearance of wet pavers.

Hanover® Pavers are designed to be a low maintenance investment. However, pavers may be sealed for preservation or color enhancement. Hanover® suggests a complete paver cleaning prior to sealing. Major stains must first be removed with specialized cleaner designed for the type of stain, followed by a cleaning of the entire area with a general cleaner. It is best to seal pavers soon after they have been thoroughly cleaned. Pavers and joints must be completely dry, clean and free of oil, grease, dust, dirt, sand, efflorescence and frost. It is advised that sealers not be applied when temperatures are below 50°F. Hanover® Sealers provide excellent protection from water, alkalis, acids, air borne pollutants and ultraviolet light, making pavers easier to clean.

COVERAGE

Rough Surface = 350 sq ft/gal @ 1.0 mil
Smooth Surface = 450 sq ft/gal @ 1.0 mil
Coverage varies based on surface porosity and texture.

NET CONTENTS

1 US Gallon (3.7853 L) or 5 US Gallon (18.9 L)
Weight/Gallon: 6.91 lb/gal
Pint size (shown in picture) is used for samples only and is not available for purchase.

APPLICATION

Intended for use in industrial and commercial applications where personal protective equipment is required and mandatory. **DO NOT USE SPRAYER.** Surface must be clean, dry, free from oil, grease, dust, dirt, sand, efflorescence and frost. HD Sealer is not sprayable and must be applied with a brush or roller. Apply over clean, dry block. Exterior applications only. Sealer may increase slipperiness. For complete application instructions, refer to product label.

Before using this product, read the Material Safety Data Sheet for additional safety precautions.
To request a Material Safety Data Sheet, call 800.426.4242 or visit www.hanoverpavers.com.

HANOVER®
Architectural Products
5000 Hanover Road, Hanover, PA 17331
717.637.0500 • fax 717.637.7145
www.hanoverpavers.com