



Hanover[®] Prest[®] Pavers for Roofs & Waterproofed Decks

Hanover[®] Prest[®] Pavers, high density pressed concrete units, are manufactured to 1/8" tolerances and produced by subjecting the concrete mix to a minimum pressure of 1,000 pounds per square inch over the entire surface area. This results in a product with the density and strength of natural stone.

Hanover[®] Prest[®] Pavers provide durability and protection for the roof or waterproofed deck system from harsh weather conditions. Hanover[®] Pavers make roofs and decks safer for pedestrians and simplify repairs. Hanover[®] Support Pedestals, together with Hanover[®] Pavers, provide effective drainage between the pavers and the system below. Hanover[®] Support Pedestals make roof and deck plazas serviceable, functional and attractive.

Dimensionally Compatible Prest [®] Paver Sizes		1 1/4"	1 1/2"	1 3/4"	2"	2 1/4"	2 1/2"	3"	4"
297mm x 297mm	11 3/4" x 11 3/4"		X	X	X	X	X	X	
297mm x 447mm	11 3/4" x 17 5/8"		X	X	X	X	X	X	
297mm x 597mm	11 3/4" x 23 1/2"		X	X	X	X	X	X	
297mm x 897mm	11 3/4" x 35 3/8"		X		X	X	X	X	
297mm x 1197mm	11 3/4" x 47 1/8"*						X	X	
447mm x 447mm	17 5/8" x 17 5/8"		X	X	X	X	X	X	X
447mm x 597mm	17 5/8" x 23 1/2"		X	X	X	X	X	X	
447mm x 897mm	17 5/8" x 35 3/8"		X		X	X	X	X	
597mm x 597mm	23 1/2" x 23 1/2"		X	X	X	X	X	X	X
597mm x 897mm	23 1/2" x 35 3/8"			X	X	X	X	X	
597mm x 1197mm	23 1/2" x 47 1/8"*						X	X	
897mm x 897mm	35 3/8" x 35 3/8"*						X	X	
Additional Prest [®] Paver Sizes		1 1/4"	1 1/2"	1 3/4"	2"	2 1/4"	2 1/2"	3"	4"
302mm x 302mm	11 7/8" x 11 7/8"		X		X	X	X	X	
303mm x 303mm	11 15/16" x 11 15/16"		X		X	X	X	X	
378mm x 378mm	14 7/8" x 14 7/8"		X		X	X	X	X	
403mm x 403mm	15 7/8" x 15 7/8"		X		X	X	X	X	
454mm x 454mm	17 7/8" x 17 7/8"		X		X	X	X	X	
597mm x 747mm	23 1/2" x 29 1/2"				X	X	X	X	
606mm x 606mm	23 7/8" x 23 7/8"		X		X	X	X	X	
606mm x 911mm	23 7/8" x 35 7/8"		X		X	X	X	X	
610mm x 610mm	24" x 24"		X		X	X	X	X	
610mm x 914mm	24" x 36"		X		X	X	X	X	
759mm x 759mm	29 7/8" x 29 7/8"				X				
908mm x 908mm	35 3/4" x 35 3/4"*						X	X	
911mm x 911mm	35 7/8" x 35 7/8"*						X		
Hexagonal, 402mm across flats	Hexagonal, 15 7/8" across flats				X	X	X	X	
Hexagonal, 609mm across flats	Hexagonal, 24" across flats				X	X	X	X	
Octagonal, 402mm across flats	Octagonal, 15 7/8" across flats				X	X	X	X	

 = Standard Thickness  = SlateFace[®] Paver Thickness (22 lbs/sf)

Please Note: Paver weight at a 2" thickness is 25 lbs/sf.

*Note increased thickness and weight for these paver sizes.

Hanover[®] Prest[®] Pavers for Roofs & Waterproofed Decks (continued)

RELATIVE STRENGTHS: (at 2" thickness)

Compressive: 8,500 psi at 28 days

Density: 155 lbs/cu. ft.

Flexural: 1,100 psi

Finish: Tudor[®]

Absorption: less than 5%

Weight: 25 lbs/sf

The test results displayed are taken from samples of Hanover's Prest[®] Pavers with a standard mix design. Hanover[®] Prest[®] Pavers, high density, hydraulically pressed concrete units, are manufactured to 1/8" tolerances and produced by subjecting the concrete mix to a minimum pressure of 1,000 pounds per square inch over the entire surface area. This results in a product with the density and strength of natural stone.

Pedestal[®] Paver

This patented paver incorporates the idea of an elevated paver drainage system with the use of an integral footed, concrete paver of the highest quality. An elevated clearance of 1/2" allows effective drainage.

Actual Size: 23 1/2" x 23 1/2" x 2 1/4"

Color: Natural

Metric Size: 597mm x 597mm x 57mm

Finish: Tudor[®]

Weight: 22 lbs/sf

Standard Colors:

Limestone Gray, Quarry Red, Cream, Tan, Brown, Red 15, Charcoal, and Natural

Custom color and aggregate blending is available on special order and when quantity ordered permits.